



SPECIFICATIONS

RESIDENTIAL SERIES M23



PRANA SERIA 150 SILENT



PRANA SERIA 150 SILENT MINI

- The characteristics of equipment indicated in the documentation were obtained in laboratory conditions.
- Some of the content can be differ from device depending on model, region, software version and there is a possibility for changes without prior notice.
- For the required model searching, press the pointer next to the required model or scroll in the standard way.



PRANA SERIA 150 SILENT M23

BALANCED VENTILATION	1/1 (NIGHT)	2/2	3/3	4/4 (REFERENCE FLOW)	5/5
FLOW RATE M ³ /H	5/5	12/12	20/20	26/26	52/52
POWER INPUT (+/- 0,2W), W	3,2	4	4,5	5,6	16,4
SOUND PRESSURE LEVELS, INDOOR, 3M, LPA	8,2	17,9	19,9	28,1	44
SOUND PRESSURE LEVELS, OUTDOOR, 3M, LPA	<8	16,9	19,1	27,5	42,7
η , +7°C	98,5	87	64,9	59,9	46,7
η , -2°C	105,3	94	84,2*	65,1*	57,4*
η , -15°C	99*	94*	90*	88*	76*
MINI-HEATING POWER INPUT (+/-3W)	45				
DRAIN-HEATING POWER INPUT**	≥6				
*WINTER-MODE **OPTIONAL, MIN LENGTH					



PRANA SERIA 150 SILENT MINI M23					
BALANCED VENTILATION	1/1 (NIGHT)	2/2	3/3	4/4 (REFERENCE FLOW)	5/5
FLOW RATE M ³ /H	5/5	12/12	20/20	26/26	52/52
POWER INPUT (+\ - 0,2W), W	3,2	4	4,5	5,6	16,4
SOUND PRESSURE LEVELS, INDOOR, 3M, LPA	8,2	17,9	19,9	28,1	44
SOUND PRESSURE LEVELS, OUTDOOR, 3M, LPA	<8	16,9	19,1	27,5	42,7
η , +7°C	79,4	71,8	53,3	46,3	37,2
η , -2°C	85,2	78,2*	59,7*	50,8*	42,4*
MINI-HEATING POWER INPUT (+\ -3W)	45				
DRAIN-HEATING POWER INPUT**	≥6				
*WINTER-MODE **OPTIONAL, MIN LENGTH					

